Tucker SNO-CAT®

MODEL 1000

TUCKER SNO-CAT®

MODEL 1000

OVERVIEW

With the lowest overall height and streamlined build, the Model 1000 was designed specifically for narrow, tight, and twisty trails. It easily navigates compact trail infrastructure without compromising durability or build quality, making it the ideal choice for agility.

FEATURES

- Thermal-Coated & Insulated 2-Passenger Cab
- 12 Volt Power Port Outlet
- Heated Side Mirrors
- LED Upper Lights High Beam x 4
- LED Backup Lights x 2
- Dual 950 CCA Batteries
- Raised Axle Housing Breather Vents
- Tilt/Telescoping Steering Wheel
- 7" Display w/ Full Engine Instruments
- Cold Start System
- AM/FM/CD Stereo w/ Bluetooth
- 36,000 B.T.U. Cab Heater
- Mechanical Drum Parking Brake
- Hydraulic Oil Heater
- F/R 2" Hitch Receivers & Rear Pintle Hitch

SPECIFICATIONS

- Engine - QSB 4.5L 130 H.P. T4F Cummins Diesel
- Transmission - Allison 2500 Automatic
- Differential - Dana 80 (4.10:1) & HD Drivelines
- Fuel Capacity - 80 Gallons
- Alternator - 160 Amp.
- Tracks - 26" x 175" Rubber Terra
- Length (w/ Blade) - 21'8"
- Width (w/ Implements) - 7'2"
- Height - 8'7"
- Rear Deck - 16" x 56"
- Curb Weight - 11,165 lbs.
- Max Deck Load - 1,000 lbs.
- Turning Radius - Approximately 26 ft.
- Ground Clearance - 15"
- Hydraulics - Power Steering & 3 Rear Circuits
- Standard equipment and full fuel w/o optional equipment, passengers, or deck load

FOLLOW US ON SOCIAL MEDIA!

CONTACT

sno-cat.com

2872 South Pacific Highway | Medford, OR, 97501

Ph (866) SNO-CAT1 | Ph (541) 779-3731 | Fx (541) 779-3735

ALL RIGHTS RESERVED - PRICES AND SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE